



# TECHNICAL DATA SHEET

# BARKIET ADHESIVE 1K-950

## Processing:

Prior to use, leave the container with the adhesive until it reaches ambient temperature. Take off foil after opening the container. Remove adhesive skin, if formed. The optimum conditions for parquet laying: temperatures between 18 and 25°C and relative air humidity between 45 and 65 %. Spread adhesive evenly on the sub-floor with a suitable toothed putty knife.

Apply only such an amount of adhesive which can be covered with parquet within 30 - 40 minutes. Place floor elements on the adhesive, press them lightly and shift horizontally. Pay special attention to proper covering of parquet bottom with adhesive.

Leave a 10 - 15 mm wide joint between the parquet and the wall. Remove wedges immediately after laying the parquet. Fresh dirty spots caused by the adhesive are to be cleaned immediately with a clean cloth. Finishing works such as grinding, lacquering or oiling can be carried out only when the adhesive is completely set and the parquet is settled in the room. The technical advisor must be contacted if the adhesive is to be used for gluing chemically modified wood, very oily kinds of exotic wood and the parquet lacquered on both sides.

Instructions and recommendations of parquet makers as well as all other valid national standards and regulations are to be followed. In case of doubts, carry out test gluing.

## Storage:

The shelf life is 12 months when the adhesive is stored in a cool and dry place.

## Safety:

Keep out of the reach of children.

EUH208 Contains N-(3-(tri-methoxysilyl)propyl)ethylene diamine, Dioctyltinbis(acetylaceton).

May cause an allergic reaction.

## Norms / atestations / certificates:

- EN 14293
- EC1plus

**Package:** 15kg

## Logistics:

Capacity 1 pcs [kg]	Weight 1 pcs [kg brutto]	Dimensions 1 pcs [kg]	Number pcs/pallet	Weight / pallet [kg]	Dimensions pallet with the goods [mm]	Weight pallet with the goods [kg]
15	15,46	256x293x257	44	680,24	1200x800x1280	701,24

## Warnings:

Waste material - leave until hardened and remove as construction waste.

## Distributor:

BARLINEK S.A., Al. Solidarności 36, 25-323 Kielce

tel.: +48 41 333 11 11, fax: +48 41 333 00 00

*The above data, recommendations and instructions are based on the best knowledge, research and experience of the product manufacturer and have been granted in good faith in accordance with the rules of the manufacturer and its suppliers. The proposed procedures are considered universal, but each user of this material should make sure in all possible ways, including checking the final product in appropriate conditions, on the suitability of the materials provided to achieve the intended purposes. Neither the manufacturer nor the distributor or their representatives can be held responsible for any loss incurred as a result of improper or incorrect use of these materials.*

*This document is informational. It does not constitute a warranty of product characteristics or quality specifications and cannot be the basis for complaint. The use of the information provided, as well as the use of the product, are not controlled by the Distributor, and therefore it is the responsibility of the user determine the safety of application.*